

#### Materials

### **ArchPolymer**<sub>TM</sub>

an artificial wood primed white easy to install with the approved adhesive and a brad nailer. Finish joining edges with poly spackling compound. Optional Class A fire rating available. Exterior & Interior use

#### GRG-NeoPlaster<sub>TM</sub>

Much stronger than tradiitonal plaster Class A fire rated product. Screw & glue into place. Priming by others. Interior use.

#### ResinMold®

A Flexible synaptic polymer for vaulted or curved ceilings Interior & Exterior Use



Height 2" 5cm

Projection 2-1/4" (5.7cm)


### **Ships World Wide**

\* All specifications subject to change without notice, Final products & Measurements may vary from this brochure



# Profile: IPNP4238 Flexible ResinMold<sub>TM</sub>

#### 1) ARCH - True 1/2 Circle & Eyebrow **Elevation Drawing**






Please Provide Inside Crown Measurements

D= Distance to Side from C Number of Arches:

## 2) CIRCLE





or Circumference

# of Circles \_\_\_\_\_



#### 3) CURVED WALL Plan View Drawings

Convex Wal	1 /

A = Depth =

|-----| Length of Curve

A = Depth =

-----|

Concave Wall

4) STRAIGHT LENGTHS

Total Feet (Meters) Required: \_\_\_\_\_